

TECHNICAL DATA SHEET (TDS)

Momtaz Bell Gostar (private joint stack) www.deltaadhesive.com

SUPER GLUE

Delta Super Glue

Delta Super Glue is a cyanoacrylate adhesive that set within seconds to form a strong bond in most of the smooth surfaces. It works well on both porous and non-porous materials. The adhesive can be used to bond tile, ceramic, porcelain, stone, glass, paper, cardboard, plastic, leather, cloth, wood, rubbers, etc. It is also resistant to moisture, most chemicals and freezing temperatures.

Characteristics

- Manufactured based on cyanoacrylate
- High adhesion strength
- Drying in a very short time
- Transparent structure
- Suitable for delicate and precise tasks due to having thin and narrow nozzle
- Resistant to the solvents such as petrol, alcohol and oil
- Resistant to water and high strength

Direction of use

For the best use, make sure the surface is dry and clean, use it in a well-ventilated area.

Put a thin layer of super glue in the desired place, the thinner the thin layer of glue, the stronger and faster the adhesion will be.

Press the glued parts together immediately and for a short time (Hold for 5-20 seconds depending on the type of surface.

After use, clean the tube head and keep it in a cool and dry place vertically (to prevent the nozzle from clogging) in order to make the glue last longer.

Storage and Shelf life

It should be kept and stored for 12 months in a cool and dry place within 5 -30 $^{\circ}$ c.

Physical & Chemical Properties

Specification	
Color	Colorless and
	Transparent
Polymer base	Cyanoacrylate
Viscosity	10-25
(at 25°c) cps	
Specific gravity	1.10
(at 25°C) g/cm ³	
PH	5

Safety and health

Keep out of reach of children. In case of contact with skin and eyes, wash with water.

Gloves, glasses and masks should be used during application, and proper ventilation should be used in the work environment. Protect from heat, light and moisture. It is a part of poisonous substances, but the dosage is very low. It is a part of poisonous substances, but the dosage is low.

Packaging

Packaging	Numbers in a box
3 g	12